TensionTec



Moralejo Técnica S.L

moralejo@moralejotecnica.com

https://moralejotecnica.com/



This device detects the fall of a general electrical switch and therefore the lack of power supply downstream in the electrical installation that is being monitored. In addition, it detects the thermal jump of a motor protection (motor protection switch). Imagine an electrical panel for a pump with an automatic switch and thermal protection for the pump motor. If the thermal trips, but not the automatic one, the pump stops working and you will receive notification of the incident on your phone. In the same way, if the main switch falls due to a short circuit or electrical overconsumption or whatever reason, you would also receive a notification.

General

- Configurable sampling time (default: 30 min.)
- Does not require recalibration or maintenance.
- Commissioning, easy and fast.

Electrical characteristics

- Electrical power supply: 2 serial batteries Li-socl2.
- Tension: 7,20 Volts.Capacity: 14400 mAh.
- Consumption:
 - < 150mA Active.< 25uA Idle.

Wireless communications

- 2G/3G/4G with SIM card.
- The antenna is external with gain -3 dB.

Wired communications

- RS-485 port.
- RS-232 port.

Aplications

- Control of electrical installations.
- Circuit breaker drop detection.
- Motor protection switch fall detection.

Equipment measurement

- Automatic magneto-thermal switch.
- Motor protector.

work environment

Temperature: -30°C to +80°C.


• Humidity: 10% to 90% RH.


Connectivities



- Our devices are available with different connectivity technologies.
- Choose the one that best suits your needs or let us advise you.
- Sigfox communications.
- LoRa communications.
- 2G/3G/4G, SIM card.
- NB-IOT.

Physical properties of the box







Protection index	IP-67
Height	72 mm
Width	145 mm
Depth	75 mm
Weight	600 gr



Moralejo Técnica S.L.

C/Vertical VI-Nº2

37188-Carbajosa de la sagrada

Tlf: (+34) 923 19 77 89

https://www.moralejotecnica.com

moralejo@moralejotecnica.com.com